



SWOCK M POWER TURN BUCKLE

Our strong one in the field of turn buckles is the Swock M Power. This model was developed by us in 1993 and is now offered in an improved form. The purpose of the Swock M Power is to reduce (tension) and release the rope length by turning the knob.

CONFIGURATION

The turn lock is provided with a transmission ratio of 5:1 achieved with an epicyclic gear. This enables a very high torque to be reached in a tight space. It's unique, with its high tension capability and therefore suitable for every application where a high load is necessary.

POSSIBLE APPLICATIONS

The application possibilities are manifold. From an alternative shoe fastener instead of laces or Velcro, to sports such as head size adjustment for a helmet, to orthopaedic applications. Thanks to the flexible cable guide, several adjustments can also be carried out via one lock, even in the most confined spaces.

USABILITY

The cable is tensioned through turning the knob clockwise (cable length shortened) and anticlockwise, relaxed again. There is also the additional „Quick Release“ function for quick complete buckle release. This is done by pressing in the centre.



PHONE +41 44 929 69 30
E-MAIL info@gudo.com
INTERNET www.gudo.com

Gass 12
CH-5242 Lupfig

CONNECTOR PLATES



CONNECTOR PLATE TYPE A
curved, narrow



CONNECTOR PLATE TYPE B
curved



CONNECTOR PLATE TYPE C
flat

FITTING

An adapter plate is used to fit the turn buckle to the product. This can be bonded, riveted or sewn in position. The turn buckle is then clicked into place. They are available in 3 versions.



SWOCK M POWER & CONNECTOR PLATE TYPE A

WIRES GUIDES/DEFLECTORS

We also have various standard rope deflectors in our range. These guide the wire in a defined position and help to achieve optimum force distribution. The wire is clicked into the guides which makes replacement or installation easy.



DEFLECTOR
TYPE 5



DEFLECTOR
TYPE 3



DEFLECTOR
TYPE 2



DEFLECTOR
TYPE 4

TECHNICAL DATAS

Power transmission:	up to 5:1
Diameter:	33 mm
Height:	17 mm
Wire diameter:	1 mm
Adjustment range:	max. 250 mm